



Side-By-Side Pipe Turning Welding Positioner Comparison

Positioner Specifications	08P-200	12P-800	12P-900
Load Capacity	300 lbs (at chuck face)	1,000 lbs (at chuck face)	1,000 lbs (at chuck face)
Dimensions	14" x 17" x 20"	26" x 26" x 26"	22" x 23" x 25"
Turning Torque	730 in-lbs	3,000 in-lbs	3,000 in-lbs
Height Adjustability	45"–69" in 4" increments	33-69" in 4" increments	48-96" in 6" increments
Power Requirements	110V, 1-ph	110V, 1-ph	110V, 1-ph
Rotation Speed	0.7 – 7.0 RPM	0.45 – 4.5 RPM	0.5 - 5 RPM
Ground Capacity	200 Amps	200 or 400 Amps	800 Amps
Table	12" OD table, 8" chuck optional	12" OD table, 12" chuck optional	12" OD table, 12" chuck optional
Thru-Bore	3/8" hollow spindle c/w air purge fitting	3" hollow thru-bore	3/8" hollow spindle c/w air purge fitting
Range of operation	Manually adjustable with handle -15°–105° in 15° increments	Hand crank self-locking worm gear tilt feature -5°–100° range c/w angle gauge	Hand crank self-locking worm gear tilt feature -5°–100° range c/w angle gauge
Equipment Mass	110 lbs	190 lbs	280 lbs